



NVIDIA QUADRO[®] FX 560

**The Definition of Performance
The Standard for Quality**

NVIDIA Quadro[®] FX 560 by PNY Technologies[®] graphics board features uncompromised performance and programmability at an entry-level price for professional CAD, DCC, and visualization applications.

NVIDIA Quadro FX 560 entry-level graphics are designed to deliver cost-effective solutions to professional 3D environments without compromising on quality, precision, performance, and programmability. Featuring advanced features ranging from a 128-bit floating point graphics pipeline, 12-bit subpixel precision, fast GDDR3 memory, and HD output, the NVIDIA Quadro FX 560 is certified on a wide set of CAD, DCC, and visualization applications, offering the value and capabilities professional users expect. In addition, support for one dual-link DVI output and HD component out enables direct connection to both high resolution digital flat panels and broadcast monitors, making the NVIDIA Quadro FX 560 a must have for any video editing solution.

The NVIDIA Quadro FX family delivers on the promise of the industry's fastest PCI Express[®] workstation graphics solution. Featuring NVIDIA Quadro FX 5500, FX 4500 X2, and FX 4500 at the ultra-high-end, NVIDIA Quadro FX



3500 and FX 3450 at the high-end, NVIDIA Quadro FX 1500 and FX 1400 at the mid-range, and NVIDIA Quadro FX 560, FX 550, and FX 350 at the entry-level, NVIDIA Quadro FX delivers unmatched workstation performance and quality. CAD and DCC applications acquire a new

level of interactivity by enabling unprecedented capabilities in programmability and precision. For the first time, styling and production rendering become integral functions of the design workflow, shortening the production process and enabling faster time to market.

PRODUCT SPECIFICATIONS

Form Factor	ATX, 4.376" x 6.8"
Frame Buffer Memory	128MB GDDR3
Memory Interface	128-bit
Memory Bandwidth	19.2GB/sec.
Max Power Consumption	30W
Graphics Bus	PCI Express x16
Display Connectors	DVI-I (DL), DVI-I, 7-pin HDTV out
HD Component Out	Yes
Auxiliary Power Connectors	Not Required
Number of Slots	1
Thermal Solution	Active Fansink

NVIDIA Quadro FX 560 Key Features and Benefits

Highest Workstation Application Performance	Next-generation architecture enables over 2x improvement in geometry and fill rates with the industry's highest performance for professional CAD, DCC, and visualization applications.
Unmatched Color Precision	Full 128-bit precision graphics pipeline enables sophisticated mathematical computations to maintain high accuracy, resulting in unmatched visual quality. Full IEEE 32-bit floating-point precision per color component (RGBA) delivers millions of color variations with the broadest dynamic range.
Next-Generation Vertex and Pixel Programmability	NVIDIA Quadro FX GPUs introduce infinite length vertex programs and dynamic flow control, removing the previous limits on complexity and structure of shader programs. With full support for Vertex and Shader Model 3.0, NVIDIA Quadro FX GPUs deliver sophisticated effects never before imagined for real-time graphics systems.
Unparalleled Subpixel Precision	12-bit subpixel precision delivers high geometric accuracy, eliminating speckles, cracks, and other rasterization anomalies.
Hardware-Accelerated Pixel Read-Back	Greater than 2.4GB/sec., pixel read-back performance delivers massive host throughput, more than 10x the performance of previous generation graphics systems.
Rotated Grid FSAA (FSAA)	RG FSAA sampling algorithm introduces far greater sophistication in the sampling pattern, significantly increasing color accuracy and visual quality for edges and lines, reducing "jaggies" while maintaining performance.
High Precision Dynamic Range Imaging (HPDR) technology	Sets new standards for image clarity and quality through floating point capabilities in shading, filtering, texturing, and blending. Enables unprecedented rendered image quality for visual effects processing.
NVIDIA PureVideo Technology	NVIDIA® PureVideo™ technology is the combination of high-definition video processors and software that delivers unprecedented picture clarity, smooth video, accurate color, and precise image scaling for SD and HD video content. Features include, high-quality scaling, spatial temporal de-interlacing, inverse telecine, and high quality HD video playback from DVD.
Integrated HD Component/S-Video	7-pin HDTV out connector and break-out cable provide graphics to component (YPrPb) or S video out to enables real-time output to HDTVs, broadcast monitors, or Video recorders for digital video, medical imaging, and simulation capture. Supported Formats: Component Mode: YPrPB – SMPTE 1080i, 720p, 480p, 576p Composite Mode: NTSC/PAL 480i, 576i

PRODUCT SPECIFICATIONS

Supported Operating Systems

- Microsoft® Windows® XP (64-bit and 32-bit)
- Microsoft Windows 2000 (32-bit)
- Linux® - Full OpenGL® implementation, complete with NVIDIA and ARB extensions (64-bit and 32-bit)
- AMD64, Intel EM64T

NVIDIA Quadro FX 560 Architecture

- 128-bit color precision
- Unlimited fragment instruction
- Unlimited vertex instruction
- 3D volumetric texture support
- Single-system powerwall
- 12 pixels per clock rendering engine
- Hardware accelerated antialiased points and lines
- Hardware OpenGL overlay planes
- Hardware accelerated two-sided lighting
- Hardware accelerated clipping planes

- 3rd-generation occlusion culling
- 16 textures per pixel in fragment programs
- Window ID Clipping Functionality
- Hardware Accelerated Line Stippling

Shading Architecture

- Fully programmable GPU (OpenGL2.0/ DirectX 9.0c class)
- Long fragment programs (unlimited instructions)
- Long vertex programs (unlimited instructions)
- Looping and subroutines (up to 256 loops per vertex program)
- Dynamic flow control
- Conditional execution

High Level Shader Languages

- Optimized compiler for Cg and Microsoft® HLSL
- OpenGL 2.0 and DirectX 9.0c support
- Open source compiler

High-Resolution Antialiasing

- 12-bit subpixel sampling precision enhances AA quality
- Rotated Grid Full-Scene Antialiasing (RG FSAA)

Display Resolution Support

- 1 Dual Link + 1 Single Link DVI-I outputs drive digital displays at resolutions up to 1900 x 1200 @ 60Hz with single link
- Maximum Digital resolution of 3840 x 2400 (24 Hz) through the dual link DVI connector
- Internal 400 MHz DACs-Two analog displays up to 2048x1536 @ 85 Hz

NVIDIA nView Architecture

- Advanced multi-display desktop and application management seamlessly integrated into Microsoft Windows.



Where to buy NVIDIA Quadro by PNY Technologies

NVIDIA Quadro by PNY is available through distribution, reseller, and SI partners. Please visit <http://www.pny.com/products/quadro/>

PNY Technologies | 299 Webro Road | Parsippany, NJ 07054-0218 | T 973.515.9700 | F 973.560.5590 | www.pny.com

©2006 NVIDIA Corporation. NVIDIA, the NVIDIA logo, NVIDIA Quadro, and PureVideo are trademarks and/or registered trademarks of NVIDIA Corporation. All rights reserved.
©2006 PNY Technologies. The PNY Technologies logo is a registered trademark of PNY Technologies. All rights reserved. All company and product names are trademarks and/or registered trademarks of the respective owners with which they are associated. Features, pricing, availability, and specifications are all subject to change without notice.